

Fujitsu fi-6000NS ML

The fi-6000NS ML combines the intuitive user interface and speed of a desktop scanner with the high productivity and advantages of a network scanner. The 8.4-inch touch screen and integrated keypad (US101 + Multi Lingual Overlay) make the fi-6000NS ML network scanner very easy to use, while the scan-to-mail mode allows scanned documents to be sent to network folders or via the net fax system. Users can also generate password protected PDF documents from fi-6000NS scans, and the automatic image processing feature automatically rotates and straightens documents and removes blank pages.

Working Environment

The fi-6000NS ML is easily connected to the office network using the standard RJ-45 10/100Base-TX interface of the scanner. The fi-6000NS is particularly suited to small businesses looking for an easy to use, flexible desktop scanner for all daily scan tasks.

Top Features

- Scanned documents can be sent via email (scan-to-mail), to network folders, to network printers (scan-to-print), by fax (scan-to fax) or to your application with the SDK
- The scanned image can be sent as a JPEG, TIFF, MTIFF or PDF attachment. The PDF can be made searchable by the in-built OCR software before transmission, for additional security the PDF can also be password protected.
- Automatic Image Processing: Automatic page size detection, document rotation, deskew, colour recognition and blank page removal
- Ultrasonic double-feed detection
- Dual CCD-Scanning-Elements: detect even the smallest details in colour, greyscale or black and white
- Operation via 24bit colour, 8.4-inch high resolution XGA touch screen with zoom/image rotation function and International hardware keyboard



Included

- Keyboard Cover (UK, German, French, Italian and Spanish)
- User Manual
- AC Adapter and power cable
- Ethernet cable

Accessories (not included)

- SDK (free of charge, available upon request)

Scanning mode	Duplex	
Document feed	ADF (50 sheets capacity)	
Document size	Credit cards to A4 (long documents to 863 mm)	
Optical resolution	600dpi (CCD-Sensor)	
Speed (A4, Portrait)	Simplex	Duplex
B/W (200dpi)	25ppm	50ipm
Colour (150dpi)	30ppm	60ipm
Interface	RJ-45 (10Base-T/100Base-TX)	
Network protocols	TCP/IP, DHCP, SMTP, SMB, LDAP and SNTF	
Dimensions (WxDxH)	315 x 390 x 275 mm	
Weight	13 kg	
Noise level (operating)	< 50 dB(A)	
Noise level (stand-by)	< 6.5 dB(A)	